

Commonwealth of Kentucky
Natural Resources and Environmental Protection Cabinet
Department for Environmental Protection
Division for Air Quality
803 Schenkel Lane
Frankfort, Kentucky 40601
(502) 573-3382

AIR QUALITY PERMIT

Permittee Name: RAYLOC, Division of Genuine Parts Company
Mailing Address: P.O. Box 530 Morganfield, Kentucky 42437

Source Name: RAYLOC
Mailing Address: Same

Source Location: US 60 East, Morganfield

Permit Type: Federally-Enforceable
Review Type: Title V

Permit Number: V-98-043
Log Number: F481
Application
Complete Date: January 20, 1998

KYEIS ID #: 077-3900-0018
AFS Plant ID #: 21-225-00018
SIC Code: 7539

Region: Owensboro
County: Union

Issuance Date: May 7, 1999

Expiration Date: May 7, 2004

TABLE OF CONTENTS

<u>SECTION</u>		<u>DATE OF ISSUANCE</u>	<u>PAGE</u>
SECTION A	PERMIT AUTHORIZATION	May 7, 1999	1
SECTION B	EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS	May 7, 1999	2
SECTION C	INSIGNIFICANT ACTIVITIES	May 7, 1999	30
SECTION D	SOURCE EMISSION LIMITATIONS AND TESTING REQUIREMENTS	May 7, 1999	31
SECTION E	SOURCE CONTROL EQUIPMENT OPERATING REQUIREMENTS	May 7, 1999	32
SECTION F	MONITORING, RECORD KEEPING, AND REPORTING REQUIREMENTS	May 7, 1999	33
SECTION G	GENERAL CONDITIONS	May 7, 1999	36
SECTION H	ALTERNATE OPERATING SCENARIOS	May 7, 1999	40
SECTION I	COMPLIANCE SCHEDULE	May 7, 1999	40
ATTACHMENT A	401 KAR 63:460, National emissions standards for halogenated solvent cleaning (40 CFR 63 SUBPART T).		

SECTION A - PERMIT AUTHORIZATION

Pursuant to a duly submitted application which was determined to be complete on January 20, 1998, the Kentucky Division for Air Quality hereby authorizes the operation of the equipment described herein in accordance with the terms and conditions of this permit. This permit has been issued under the provisions of Kentucky Revised Statutes Chapter 224 and regulations promulgated pursuant thereto and shall become the final permit unless the U.S. EPA files an objection pursuant to Regulation 401 KAR 50:035, Section 21(3).

The permittee shall not construct, reconstruct, or modify any affected facilities without first having submitted a complete application and receiving a permit for the planned activity from the permitting authority, except as provided in this permit or in the Regulation 401 KAR 50:035, Permits.

Issuance of this permit does not relieve the permittee from the responsibility of obtaining any other permits, licenses, or approvals required by this Cabinet or any other federal, state, or local agency.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS

01 (SB-1)

Dip Tanks and Spray Booth

Description:

Dip Coating and Spray Painting of Starter Cases
350 pieces per hour
Construction commenced: 1985
Equipped with paper filters

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations

Emissions of particulate matter shall not exceed 2.34 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None.

3. Testing Requirements continued:

None.

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above).

6. Specific Reporting Requirements:

Semi-annual reports of the method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

02 (SB-2)

Dip Tank

Description:

Dip Painting (Resin Coating) of Automotive Rotors and Stators:

175 pieces per hour

Construction commenced: 1977

APPLICABLE REGULATIONS:

None

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

None

3. Testing Requirements:

None

4. Specific Monitoring Requirements:

None

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above).

6. Specific Reporting Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

03 (SB-3)

Spray Booth

Description:

Spray painting of Automotive Starters:

100 pieces per hour

Construction commenced: 1985

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.34 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above)

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

- 6.** Semi-annual reports of the method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

04 (SB-4)

Spray Booth

Description:

Spray painting of windshield wiper motors:

160 pieces per hour

Construction commenced 1989

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.34 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None

3. Testing Requirements continued:

None

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above)

6. Specific Reporting Requirements:

Semi-annual reports of the method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

05 (E-5)

Armature Oven/Wave Soldering

Description:

Wave Soldering of Starter Armatures
25 pieces per hour
Construction commenced 1985

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.34 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

5. Specific Recordkeeping Requirements:

None.

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

06 (E-6)

Dip Tank

Description:

Resin Coating of Electrical Rotors and Stators
175 pieces per hour
Construction commenced 1974

APPLICABLE REGULATIONS:

None.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

None.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

None.

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above).

6. Specific Reporting Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

07 (E-7)

Paint Booths

Description:

Spray painting of Alternator Stators
400 pieces per hour
Construction commenced 1990

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.34 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above).

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

27 (E-9)

Degreaser

Description:

Heated Trichloroethylene Degreasing of miscellaneous metal parts

1,600 pieces per hour

Construction commenced 1974

APPLICABLE REGULATIONS:

401 KAR 63:460, National emission standards for halogenated solvent cleaning.

(40 CFR 63 Subpart T)

1. Operating Limitations:

Regulation 401 KAR 63:460 (40 CFR 63 Subpart T) requirements:

40 CFR 63 Subpart T is incorporated as attachment A to this permit.

The permittee shall comply with the applicable requirements in 40 CFR 63.463 Batch vapor and in-line cleaning machine standards

2. Emission Limitations:

None.

3. Testing Requirements:

The permittee shall comply with the applicable requirements in 40 CFR 63.465 Test methods.

4. Specific Monitoring Requirements:

The permittee shall comply with the applicable requirements in 40 CFR 63.466 Monitoring procedures.

5. Specific Recordkeeping Requirements:

The permittee shall comply with the applicable requirements in 40 CFR 63.467 Recordkeeping requirements.

6. Specific Reporting Requirements:

The permittee shall comply with the applicable requirements in 40 CFR 63.468 Reporting requirements. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

25 (BO-13)

BACO OVEN

Description:

Baco Oven burn off grease and dirt
600 pieces per hour
Construction commenced 1986
Equipped with Afterburner

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 5.85 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

5. Specific Recordkeeping Requirements:

None.

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

32 (DB-10, DB-11, DB-12)

Debonding

Description:

Debonding (burn off) of brake shoe liners

400 pieces per hour

Construction commenced prior to July 2, 1975

Equipped with Afterburner

APPLICABLE REGULATIONS:

401 KAR 61:020, Existing process operations which commenced before July 2, 1975.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.58 lbs/hr from each oven.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 40 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

5. Specific Recordkeeping Requirements:

None.

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

33 (CEC-14)

Burn off Oven

Description:

Burn off Oven grease and dirt
600 pieces per hour
Construction commenced 1997
Equipped with Afterburner

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.34 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

5. Specific Recordkeeping Requirements:

None.

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

34 (V-1, V-2, V-3, V-4, V-5, V-6)

Vibratory Tumbling (6)

Description:

Six Vibratory Tumbling Units

4,800 pieces per hour

Construction commenced 1986 (2) and 1990 (4)

APPLICABLE REGULATIONS:

None.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

None.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

None.

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above).

6. Specific Reporting Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

18, 19 (DC-1, DC-2, DC-3))

Shot Blasting

Description:

Wheelabrator Shot Cleaning
2,000 pieces per hour
Total of Five Units
Construction commenced 1974
Equipped with filter units

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.
401 KAR 61:020, Existing process operations which commenced before July 2, 1975.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 3.23 lbs/hr from each shot blaster constructed before July 2, 1975 and 2.88 lbs/hr from each shot blaster constructed after July 2, 1997.

Opacity of visible emissions shall not equal or exceed 40 % for each shot blaster constructed before July 2, 1975 and 20% for each shot blaster constructed after July 2, 1975.

Proper operation of the filter units shall be deemed compliance with these standards.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

The filter units shall be inspected for proper operation semiannually. Preventive maintenance shall be performed in accordance with the manufacturers recommendations. The following parameters shall be specifically inspected:

1. Filters - Replace in accordance with manufacturers recommendations.
2. Gaskets and Seals.
3. Filter cleaning mechanism.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

5. Specific Recordkeeping Requirements:

A log of the results of the filter unit inspections shall be maintained onsite and made available to Division personnel upon request.

6. Specific Reporting Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

35 (DC-4)

Brakeshoe Grinding

Description:

Three Brakeshoe Grinders
1950 pieces per hour
Construction commenced 1974
Equipped with a filter unit

APPLICABLE REGULATIONS:

401 KAR 61:020, Existing process operations which commenced before July 2, 1975.
401 KAR 58:025. Asbestos Standards (40 CFR 61 Subpart M).

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.58 lbs/hr from each grinder.
Compliance with the opacity limitation shall be deemed compliance with this standard.

Pursuant to 40 CFR 61.147 Standard for Fabricating, there shall be no visible emissions to the outside air from any of the operations (using asbestos containing materials) or from any building or structure in which they are conducted or from any fugitive sources.

Opacity of visible emissions shall not equal or exceed 40 %. (operations not using asbestos containing materials).

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below. In addition, the permittee shall perform weekly visible emissions observations. If visible emissions are detected, a Method 9 reading shall be performed. This requirement is in addition to and not in lieu of the semi-annual Method 9 readings.

3. Testing Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings and weekly visible emission observations.

The filter units shall be inspected for proper operation semiannually. Preventive maintenance shall be performed in accordance with the manufacturers recommendations. The following parameters shall be specifically inspected:

1. Filters - Replace in accordance with manufacturers recommendations.
2. Gaskets and Seals.
3. Filter cleaning

5. Specific Recordkeeping Requirements:

A log of the results of the filter unit inspections and weekly visible emissions observations shall be maintained onsite and made available to Division personnel upon request.

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings and others required in 2 above shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

28, 29, 30, 31 (T-5)

Brakeshoe Riveting

Description:

Troit Riveting
2,570 pieces per hour
Construction commenced 1985
Equipped with filter unit

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.
401 KAR 58:025. Asbestos Standards (40 CFR 61 Subpart M).

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.34 lbs/hr.
Compliance with the opacity limitation shall be deemed compliance with this standard.

Pursuant to 40 CFR 61.147 Standard for Fabricating, there shall be no visible emissions to the outside air from any of the operations (using asbestos containing materials) or from any building or structure in which they are conducted or from any fugitive sources.

Opacity of visible emissions shall not equal or exceed 20 %. (operations not using asbestos containing materials).

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below. In addition, the permittee shall perform weekly visible emissions observations. If visible emissions are detected, a Method 9 reading shall be performed. This requirement is in addition to and not in lieu of the semi-annual Method 9 readings.

3. Testing Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings and weekly visible emission observations.

The filter units shall be inspected for proper operation semiannually. Preventive maintenance shall be performed in accordance with the manufacturers recommendations. The following parameters shall be specifically inspected:

1. Filters - Replace in accordance with manufacturers recommendations.
2. Gaskets and Seals.
3. Filter cleaning

5. Specific Recordkeeping Requirements:

A log of the results of the filter unit inspections and weekly visible emissions observations shall be maintained onsite and made available to Division personnel upon request.

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings and others required in 2 above shall be reported to the Division for Air Quality's Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

36 (E-15)

Dip Tank

Description:

Antirust Coating of Brake Shoes
1,500 pieces per hour
Construction commenced 1974

APPLICABLE REGULATIONS:

None.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

None.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

None.

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above).

6. Specific Reporting Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

37 (T-15)

Spray Booths

Description:

Touch-up painting of various parts using Aerosol Cans
Construction commenced: 1985, 1989, and 1990

APPLICABLE REGULATIONS:

401 KAR 59:010, New process operations which commenced on or after July 2, 1975.

State-Origin Applicable Requirements:

The permittee shall maintain, on site, documentation from the manufacturer of each coating, solvent and clean up solvent which indicates the VOC and HAP content and make them available to Division personnel upon request.

1. Operating Limitations:

None.

2. Emission Limitations:

Emissions of particulate matter shall not exceed 2.34 lbs/hr.

Compliance with the opacity limitation shall be deemed compliance with this standard.

Opacity of visible emissions shall not equal or exceed 20 %.

Compliance shall be demonstrated via the semi-annual Method 9 reading found in item 4 Specific Monitoring Requirements below.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

The permittee shall perform semi-annual method 9 opacity readings.

5. Specific Recordkeeping Requirements:

None. (See State Origin Requirements above).

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

6. Specific Reporting Requirements:

Semi-annual method 9 opacity readings shall be reported to the Division for Air Quality=s Owensboro office. See Section F, condition 5.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

38 (CDO1)

Dip Tank

Description:

Antirust Coating of Calipers
Construction commenced 1984

APPLICABLE REGULATIONS:

None.

1. Operating Limitations:

None.

2. Emission Limitations:

None.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

None.

5. Specific Recordkeeping Requirements:

None.

6. Specific Reporting Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

39 (WMA1)

Dip Tanks (Two Tanks)

Description:

Antirust Coating of Wiper Motors
Construction commenced 1991

APPLICABLE REGULATIONS:

None.

1. Operating Limitations:

None.

2. Emission Limitations:

None.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

NA

5. Specific Recordkeeping Requirements:

None.

6. Specific Reporting Requirements:

None.

SECTION B - EMISSION POINTS, EMISSIONS UNITS, APPLICABLE REGULATIONS, AND OPERATING CONDITIONS (CONTINUED)

40 (WMC1)

Wiper Motor Cleaner

Description:

Cleaning of Wiper Motors
Construction commenced 1991

APPLICABLE REGULATIONS:

None.

1. Operating Limitations:

None.

2. Emission Limitations:

None.

3. Testing Requirements:

None.

4. Specific Monitoring Requirements:

None.

5. Specific Recordkeeping Requirements:

None.

6. Specific Reporting Requirements:

None.

SECTION C - INSIGNIFICANT ACTIVITIES

The following listed activities have been determined to be insignificant activities for this source pursuant to Regulation 401 KAR 50:035, Section 5(4). While these activities are designated as insignificant, the permittee must comply with the applicable regulation and some minimal level of periodic monitoring may be necessary.

<u>Description</u>	<u>Generally Applicable Regulation</u>
1. Natural Gas Fired Burner	59:015
2. Combustion source flame safety purging on start-up	NA
3. Application of oils, greases, lubricants or other non-volatile materials applied as temporary protective coatings	NA
4. Replacement or repair of electrostatic precipitators, bags in baghouses and filters in other air filtration equipment	59:010
5. Paved and unpaved roads and parking lots with public access.	63:010
6. Brakeshoe Liner Chipping Operation	59:010
7. Parts Washers	NA
8. Bonder Oven	NA
9. Shot Blasters	59:010
10. Space and Process Heaters	59:015
11. Cleaning Department Dip Operation	NA

SECTION D - SOURCE EMISSION LIMITATIONS AND TESTING REQUIREMENTS

PM and VOC emissions, as measured by methods referenced in 401 KAR 50:015, Section 1, shall not exceed the respective limitations specified herein.

SECTION E - SOURCE CONTROL EQUIPMENT REQUIREMENTS

Pursuant to 401 KAR 50:055, Section 2(5), at all times, including periods of startup, shutdown and malfunction, owners and operators shall, to the extent practicable, maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the division which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source.

SECTION F - MONITORING, RECORD KEEPING, AND REPORTING REQUIREMENTS

1. When continuing compliance is demonstrated by periodic testing or instrumental monitoring, the permittee shall compile records of required monitoring information that include:
 - a. Date, place as defined in this permit, and time of sampling or measurements.
 - b. Analyses performance dates;
 - c. Company or entity that performed analyses;
 - d. Analytical techniques or methods used;
 - e. Analyses results; and
 - f. Operating conditions during time of sampling or measurement;
2. Records of all required monitoring data and support information, including calibrations, maintenance records, and original strip chart recordings, and copies of all reports required by the Division for Air Quality, shall be retained by the permittee for a period of five years and shall be made available for inspection upon request by any duly authorized representative of the Division for Air Quality. [401 KAR 50:035, Permits, Section 7(1)(d)2 and 401 KAR 50:035, Permits, Section 7(2)(c)]
3. In accordance with the requirements of Regulation 401 KAR 50:035, Permits, Section 7(2)(c) the permittee shall allow the Cabinet or authorized representatives to perform the following:
 - a. Enter upon the premises where a source is located or emissions-related activity is conducted, or where records are kept;
 - b. Have access to and copy, at reasonable times, any records required by the permit:
 - i. During normal office hours, and
 - ii. During periods of emergency when prompt access to records is essential to proper assessment by the Cabinet;
 - c. Inspect, at reasonable times, any facilities, equipment (including monitoring and pollution control equipment), practices, or operations required by the permit. Reasonable times shall include, but are not limited to the following:
 - i. During all hours of operation at the source,
 - ii. For all sources operated intermittently, during all hours of operation at the source and the hours between 8:00 a.m. and 4:30 p.m., Monday through Friday, excluding holidays, and
 - iii. During an emergency; and
 - d. Sample or monitor, at reasonable times, substances or parameters to assure compliance with the permit or any applicable requirements. Reasonable times shall include, but are not limited to the following:
 - i. During all hours of operation at the source,
 - ii. For all sources operated intermittently, during all hours of operation at the source and the hours between 8:00 a.m. and 4:30 p.m., Monday through Friday, excluding holidays, and
 - iii. During an emergency.
4. No person shall obstruct, hamper, or interfere with any Cabinet employee or authorized representative while in the process of carrying out official duties. Refusal of entry or access may constitute grounds for permit revocation and assessment of civil penalties.

SECTION F - MONITORING, RECORD KEEPING, AND REPORTING REQUIREMENTS (CONTINUED)

5. Reports of any monitoring required by this permit, other than continuous emission or opacity monitors, shall be reported to the division's Owensboro Regional Office no later than the six-month anniversary date of this permit and every six months thereafter during the life of this permit, unless otherwise stated in this permit. The permittee may shift to semi-annual reporting on a calendar year basis upon approval of the regional office. If calendar year reporting is approved, the semi-annual reports are due January 30th and July 30th of each year. Data from the continuous emission and opacity monitors shall be reported to the Technical Services Branch in accordance with the requirements of Regulation 401 KAR 59:005, General Provisions, Section 3(3). All reports shall be certified by a responsible official pursuant to Section 6(1) of Regulation 401 KAR 50:035, Permits. All deviations from permit requirements shall be clearly identified in the reports.
6.
 - a. In accordance with the provisions of Regulation 401 KAR 50:055, Section 1 the owner or operator shall notify the Division for Air Quality's Owensboro Regional Office concerning startups, shutdowns, or malfunctions as follows:
 1. When emissions during any planned shutdowns and ensuing startups will exceed the standards notification shall be made no later than three (3) days before the planned shutdown, or immediately following the decision to shut down, if the shutdown is due to events which could not have been foreseen three (3) days before the shutdown.
 2. When emissions due to malfunctions, unplanned shutdowns and ensuing startups are or may be in excess of the standards notification shall be made as promptly as possible by telephone (or other electronic media) and shall cause written notice upon request.
 - b. In accordance with the provisions of Regulation 401 KAR 50:035, Section 7(1)(e)2, the owner or operator shall promptly report deviations from permit requirements including those attributed to upset conditions (other than emission exceedances covered by general condition 6 a. above) to the Division for Air Quality's Owensboro Regional Office. Prompt reporting shall be defined as follows: within three working days.
7. Pursuant to Regulation 401 KAR 50:035, Permits, Section 7(2)(b), the permittee shall certify compliance with the terms and conditions contained in this permit, annually on the permit issuance anniversary date or by January 30th of each year if calendar year reporting is approved by the regional office, by completing and returning a Compliance Certification Form (DEP 7007CC) (or an approved alternative) to the Division for Air Quality's Owensboro Regional Office and the U.S. EPA in accordance with the following requirements:
 - a. Identification of each term or condition of the permit that is the basis of the certification;
 - b. The compliance status regarding each term or condition of the permit;
 - c. Whether compliance was continuous or intermittent; and
 - d. The method used for determining the compliance status for the source, currently and over the reporting period, pursuant to 401 KAR 50:035, Section 7(1)(c),(d), and (e).

SECTION F - MONITORING, RECORD KEEPING, AND REPORTING REQUIREMENTS (CONTINUED)

- e. The certification shall be postmarked by the thirtieth (30) day following the applicable permit issuance anniversary date. Annual compliance certifications should be mailed to the following addresses:

**Division for Air Quality
3032 Alvey Park Drive W.
Suite 700
Owensboro, Kentucky 42303**

**U.S. EPA Region IV
Air Enforcement Branch
Atlanta Federal Center
61 Forsyth St.
Atlanta, GA 30303-8960**

**Division for Air Quality
Central Files
803 Schenkel Lane
Frankfort, KY 40601**

8. In accordance with Regulation 401 KAR 50:035, Section 23, the permittee shall provide the division with all information necessary to determine its subject emissions within thirty (30) days of the date the KEIS emission report is mailed to the permittee.
9. Pursuant to Section VII.3 of the policy manual of the Division for Air Quality as referenced by Regulation 401 KAR 50:016, Section 1(1), results of performance test(s) required by the permit shall be submitted to the division by the source or its representative within forty-five days after the completion of the fieldwork.

SECTION G - GENERAL CONDITIONS

(a) General Compliance Requirements

1. The permittee shall comply with all conditions of this permit. A noncompliance shall be (a) violation(s) of state regulation 401 KAR 50:035, Permits, Section 7(3)(d) and for federally enforceable permits is also a violation of Federal Statute 42 USC 7401 through 7671q (the Clean Air Act and is grounds for enforcement action including but not limited to the termination, revocation and reissuance, or revision of this permit.
2. The filing of a request by the permittee for any permit revision, revocation, reissuance, or termination, or of a notification of a planned change or anticipated noncompliance, shall not stay any permit condition.
3. This permit may be revised, revoked, reopened and reissued, or terminated for cause. The permit will be reopened for cause and revised accordingly under the following circumstances:
 - a. If additional applicable requirements become applicable to the source and the remaining permit term is three (3) years or longer. In this case, the reopening shall be completed no later than eighteen (18) months after promulgation of the applicable requirement. A reopening shall not be required if compliance with the applicable requirement is not required until after the date on which the permit is due to expire, unless this permit or any of its terms and conditions have been extended pursuant to Regulation 401 KAR 50:035, Section 12(2)(c);
 - b. The Cabinet or the U. S. EPA determines that the permit must be revised or revoked to assure compliance with the applicable requirements;
 - c. The Cabinet or the U. S. EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit;

Proceedings to reopen and reissue a permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of the permit for which cause to reopen exists. Reopenings shall be made as expeditiously as practicable. Reopenings shall not be initiated before a notice of intent to reopen is provided to the source by the division, at least thirty (30) days in advance of the date the permit is to be reopened, except that the division may provide a shorter time period in the case of an emergency.

4. The permittee shall furnish to the division, in writing, information that the division may request to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit, or to determine compliance with the permit. [401 KAR 50:035, Permits, Section 7(2)(b)3e and 401 KAR 50:035, Permits, Section 7(3)(j)]
5. The permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to the permitting authority.

SECTION G - GENERAL CONDITIONS (CONTINUED)

6. Any condition or portion of this permit which becomes suspended or is ruled invalid as a result of any legal or other action shall not invalidate any other portion or condition of this permit. [401 KAR 50:035, Permits, Section 7(3)(k)]
7. The permittee shall not use as a defense in an enforcement action the contention that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance. [401 KAR 50:035, Permits, Section 7(3)(e)]
8. Except as identified as state-origin requirements in this permit, all terms and conditions contained herein shall be enforceable by the United States Environmental Protection Agency and citizens of the United States.
9. This permit shall be subject to suspension if the permittee fails to pay all emissions fees within 90 days after the date of notice as specified in 401 KAR 50:038, Section 3(6). [401 KAR 50:035, Permits, Section 7(3)(h)]
10. Nothing in this permit shall alter or affect the liability of the permittee for any violation of applicable requirements prior to or at the time of permit issuance. [401 KAR 50:035, Permits, Section 8(3)(b)]
11. This permit shall not convey property rights or exclusive privileges. [401 KAR 50:035, Permits, Section 7 (3)(g)]
12. Issuance of this permit does not relieve the permittee from the responsibility of obtaining any other permits, licenses, or approvals required by the Kentucky Cabinet for Natural Resources and Environmental Protection or any other federal, state, or local agency.
13. Nothing in this permit shall alter or affect the authority of U.S. EPA to obtain information pursuant to Federal Statute 42 USC 7414, Inspections, monitoring, and entry. [401 KAR 50:035, Permits, Section 7(2)(b)5]
14. Nothing in this permit shall alter or affect the authority of U.S. EPA to impose emergency orders pursuant to Federal Statute 42 USC 7603, Emergency orders. [401 KAR 50:035, Permits, Section 8(3)(a)]
15. Permit Shield: Except as provided in State Regulation 401 KAR 50:035, Permits, compliance by the affected facilities listed herein with the conditions of this permit shall be deemed to be compliance with all applicable requirements identified in this permit as of the date of issuance of this permit.

SECTION G - GENERAL CONDITIONS (CONTINUED)**(b) Permit Expiration and Reapplication Requirements**

This permit shall remain in effect for a fixed term of five (5) years following the original date of issue. Permit expiration shall terminate the source's right to operate unless a timely and complete renewal application has been submitted to the division at least six months prior to the expiration date of the permit. Upon a timely and complete submittal, the authorization to operate within the terms and conditions of this permit, including any permit shield, shall remain in effect beyond the expiration date, until the renewal permit is issued or denied by the division. [401 KAR 50:035, Permits, Section 12]

(c) Permit Revisions

1. A minor permit revision procedure may be used for permit revisions involving the use of economic incentive, marketable permit, emission trading, and other similar approaches, to the extent that these minor permit revision procedures are explicitly provided for in the SIP or in applicable requirements and meet the relevant requirements of Regulation 401 KAR 50:035, Section 15.
2. This permit is not transferable by the permittee. Future owners and operators shall obtain a new permit from the Division for Air Quality. The new permit may be processed as an administrative amendment if no other change in this permit is necessary, and provided that a written agreement containing a specific date for transfer of permit responsibility coverage and liability between the current and new permittee has been submitted to the permitting authority thirty (30) days in advance of the transfer.

(d) Emergency Provisions

1. An emergency shall constitute an affirmative defense to an action brought for noncompliance with the technology-based emission limitations if the permittee demonstrates through properly signed contemporaneous operating logs or other relevant evidence that:
 - a. An emergency occurred and the permittee can identify the cause of the emergency;
 - b. The permitted facility was at the time being properly operated;
 - c. During an emergency, the permittee took all reasonable steps to minimize levels of emissions that exceeded the emissions standards or other requirements in the permit; and,
 - d. The permittee notified the division as promptly as possible and submitted written notice of the emergency to the division within two working days after the time when emission limitations were exceeded due to the emergency. The notice shall meet the requirements of 401 KAR 50:035, Permits, Section 7(1)(e)2, and include a description of the emergency, steps taken to mitigate emissions, and the corrective actions taken. This requirement does not relieve the source of any other local, state or federal notification requirements.
2. Emergency conditions listed in General Condition (d)1 above are in addition to any emergency or upset provision(s) contained in an applicable requirement.

SECTION G - GENERAL CONDITIONS (CONTINUED)

3. In an enforcement proceeding, the permittee seeking to establish the occurrence of an emergency shall have the burden of proof. [401 KAR 50:035, Permits, Section 9(3)]

(e) Acid Rain Program Requirements

If an applicable requirement of Federal Statute 42 USC 7401 through 7671q (the Clean Air Act) is more stringent than an applicable requirement promulgated pursuant to Federal Statute 42 USC 7651 through 7651o (Title IV of the Act), both provisions shall apply, and both shall be state and federally enforceable.

(f) Risk Management Provisions

1. The permittee shall comply with all applicable requirements of 40 CFR Part 68, Risk Management Plan provisions. If required, the permittee shall:
 - a. Submit a Risk Management Plan to U.S.EPA, Region IV with a copy to this division and comply with the Risk Management Program by June 21, 1999 or a later date specified by the U.S.EPA.
 - b. Submit additional relevant information if requested by the division or the U.S. EPA.

(g) Ozone depleting substances

1. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR 82, Subpart F, except as provided for Motor Vehicle Air Conditioners (MVACs) in Subpart B:
 - a. Persons opening appliances for maintenance, service, repair, or disposal shall comply with the required practices contained in 40 CFR 82.156.
 - b. Equipment used during the maintenance, service, repair, or disposal of appliances shall comply with the standards for recycling and recovery equipment contained in 40 CFR 82.158.
 - c. Persons performing maintenance, service, repair, or disposal of appliances shall be certified by an approved technician certification program pursuant to 40 CFR 82.161.
 - d. Persons disposing of small appliances, MVACs, and MVAC-like appliances (as defined at 40 CFR 82.152) shall comply with the recordkeeping requirements pursuant to 40 CFR 82.166.
 - e. Persons owning commercial or industrial process refrigeration equipment shall comply with the leak repair requirements pursuant to 40 CFR 82.156.
 - f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant shall keep records of refrigerant purchased and added to such appliances pursuant to 40 CFR 82.166.
2. If the permittee performs service on motor (fleet) vehicle air conditioners containing ozone-depleting substances, the source shall comply with all applicable requirements as specified in 40 CFR 82, Subpart B, Servicing of Motor Vehicle Air Conditioners.

SECTION H - ALTERNATE OPERATING SCENARIOS

Not Applicable

SECTION I - COMPLIANCE SCHEDULE

Not Applicable